

Amino A140



Specifications

Size and weight	114mm x 100mm x 35mm. 280g (excluding accessories and packaging)
Inputs	Ethernet 10/100 BaseT via RJ-45 shielded connector
Outputs	HDMI 1.3a. (excl. Deep colour and DTS audio) with HDCP. S/PDIF (optical). USB2.0. 10-way Mini-DIN for Composite video, Component (YPrPb), RGB, S-Video and analogue audio. RF Modulator and loop through.
Power	5V DC at 1.5A via external power supply. Less than 8W typical usage (external supply input voltage 100-240V AC 50-60Hz, 0.8A max, output 5VDC 3A)
Video resolutions	Decodes up to 720p and 1080i. Displays up to 1080p
Graphics resolutions	HD graphics up to 1280x720
Audio	Stereo audio and Dolby 5.1 surround via S/PDIF and HDMI. Dolby Digital+ pass through to external decoder

Amino A540 DVR



Specifications

Size and weight	172mm x 180mm x 48mm. 700g (excluding accessories and packaging)
Inputs	Ethernet 10/100 BaseT via RJ-45 shielded connector
Outputs	HDMI 1.3a (excl. Deep colour and DTS audio) with HDCP. 10-way Mini-DIN for Composite video, Component (YPrPb), RGB, S-Video and analogue audio.S/PDIF (optical). USB2.0. RF Modulator
Power	5V DC at 3A via external power supply Less than 12W typical usage (external supply input voltage 100-240V AC 50-60Hz, 0.8A max. Output 5V DC 3A)
Video resolutions	Decodes up to 720p and 1080i. Displays up to 1080p
Graphics resolutions	HD graphics up to 1280x720
Audio	Analogue stereo audio out. Stereo and Dolby 5.1 surround via S-PDIF and HDMI Dolby Digital+ pass through to external decoder